MATERIAL SAFETY DATA SHEET

«Share Corporation P.O. Box 245013 Milwaukee, WI 53224

GENERAL INFORMATION NUMBER: 414-355-4000 EMERGENCY TELEPHONE NUMBER: (800) 776-7192

CHEMTREC: (800) 424-9300



DATE OF ISSUE: March 31, 2004

I - Product Identification

Gasket Maker

PRODUCT CODE: 8050

CHEMICAL FORMULATION: Pressurized silicone sealer.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1

HAZARD RATING:

4 - Extreme;

3 - High;

FLAMMABILITY: 1

REACTIVITY: 0

2 - Moderate;

1 - Slight;

0 - Insignificant

· · · · · · · · · · · · · · · · · · ·						
II - Hazardous Ingredients Values reported as TWA unless noted.						
<u>%</u>	<u>PEL</u>	<u>TLV</u>	<u>302</u>	<u>355</u>	<u>372</u>	CAS#
2.00	N/E	N/E	N	N	N	4253-34-3
10.0	N/E	N/E	N	N	N	76 31-86-9
2.00	N/E	N/E	N	N	N	17689-77-9
	APPROX <u>%</u> 2.00 10.0	Values reported a APPROX OSHA <u>% PEL</u> 2.00 N/E 10.0 N/E	Values reported as TWA unless not APPROX OSHA ACGIH <u>% PEL TLV</u> 2.00 N/E N/E 10.0 N/E N/E	Values reported as TWA unless noted. APPROX OSHA ACGIH EP. <u>% PEL TLV 302</u> 2.00 N/E N/E N 10.0 N/E N/E N	Values reported as TWA unless noted. APPROX OSHA ACGIH EPA 40 C % PEL TLV 302 355 2.00 N/E N/E N N 10.0 N/E N/E N N	Values reported as TWA unless noted. APPROX OSHA ACGIH EPA 40 CFR: % PEL TLV 302 355 372 2.00 N/E N/E N N N 10.0 N/E N/E N N N

Key:

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value C: Ceiling level

STEL: Short Term Exposure Limit

N/A: Not Applicable

N/D: Not Determined

N/E: Not Established

Y: Yes N: No

302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355). 372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR = 1): N/D

SOLUBILITY IN WATER: N/D

APPEARANCE AND ODOR: Red colored caulk; mild odor.

SPECIFIC GRAVITY (WATER = 1): N/D

VOC CONTENT (% by weight): N/D

EVAPORATION RATE (WATER = 1): N/D

pH: N/D

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): > 250 (concentrate) (TEST METHOD); Open cup

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR (VOLUME %)

UPPER: N/D

LOWER: N/D

NFPA 30B Rating: N/D

EXTINGUISHING MEDIA: Water FOG foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: None

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers.

CONDITIONS TO AVOID: Excess heat and open flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None .

VI - Health Hazard Data

EYE CONTACT: X SKIN CONTACT: X ROUTES OF ENTRY INHALATION: X INGESTION: X INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None **EFFECTS OF OVEREXPOSURE**

IF IN EYES: Slight to moderate irritation with redness and swelling.

IF ON SKIN: May cause mild to moderate irritation with prolonged or repeated exposure.

IF SWALLOWED: May cause digestive comfort. IF INHALED: Irritation to eyes, nose and throat. EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Remove completely with a dry cloth or paper towel before washing with detergent and water. Get medical attention if irritation persists.

IF SWALLOWED: Contact physician or poison control center immediately.

IF INHALED: Remove person to fresh air.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and remove all sources of ignition. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal. Wash with detergent and water to reduce slipping hazard.

WASTE DISPOSAL METHOD: Consult local environmental authorities. Dispose of cans in non-incinerated trash only.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation, if recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations. LOCAL: Recommended

VENTILATION PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: None.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Do not expose to direct sunlight or store at temperatures above 120F. Do not handle contact lenses until all product has been removed from fingertips.

OTHER PRECAUTIONS: Keep out of reach of children. Do not puncture or incinerate container.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: Consumer Commodity

DOT CLASS: ORM-D

DOT ID NUMBER: None

DOT PACKING GROUP: None

MECHANICAL: Not required

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: January 2, 2003

Prepared by: PMR

DATE OF ISSUE: March 31, 2004

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.