

SAFETY DATA SHEET FOR PRESSURIZED PRODUCTS

439

SECTION I - PRODUCT IDENTIFICATION

COMPANY NAME
SPRAYWAY, INC.

Regular Telephone Number: 312-628-0998
Emergency Telephone Number: 312-628-0998

ADDRESS
484 VISTA AVE., ADDISON, IL 60101

PRODUCT TRADE NAME OR BRAND NAME
SPRAYWAY PLASTIC SPRAY

97-5432

OTHER PRODUCT DESCRIPTION OR IDENTIFICATION

COATING SPRAY 770519

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT CHEMICAL NAME	CAS #	Approx Wt.	TLV
TOLUENE	108-88-3	45	OSHA TWA= 100 PPM
DICHLOROMETHANE	75-09-2	25	OSHA TWA= 500 PPM
HYDROCARBON PROPELLANT	68476-85-7	25	ACGIH TWA= 1000 PPM

SECTION III - PHYSICAL DATA

Boiling Point: NA	Specific Gravity: 0.84
Vapor Pressure (psig): 85 @ 130° F	Percent Volatiles by Volume (%): 90
Vapor Density (AIR = 1): GREATER	Evaporation Rate (n-Butyl Acetate = 1): SLOWER
Solubility in Water: NEGLIGIBLE	
Appearance and Odor: FINE MISTY SPRAY: TOLUENE/CHLORINATED SOLVENT ODOR. DRIES TO A CLEAR FILM.	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (minimum) Method: NA	Flammable Limits in Air Volume % PROPELLANT	LEL 1.9-2.1	UEL 8.5-9.5
Extinguishing Media: DRY CHEMICAL, CO ₂			

SPECIAL FIREFIGHTING PROCEDURES: Keep containers cool. Use equipment or shielding as required to protect personnel against bursting, rupturing, or venting containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: At elevated temperatures (over 54°C/130°F) containers may vent, rupture, or burst.

PRODUCT TRADE NAME:

PRODUCT DESCRIPTION:

Unless noted otherwise, all information given is on the TOTAL PRODUCT, INCLUDING propellants.
Date Filled Out: 11-15-85 Prepared or Approved by: T. Vyff

PRODUCT BRAND NAME:

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value (TLV): SEE SECTION 11

EFFECTS OF OVEREXPOSURE: Eye contact irritating, no damage if flushed. Skin contact may cause redness or irritation. Excessive inhalation may cause dizziness.

EMERGENCY AND FIRST AID PROCEDURES: If unconscious, remove victim to fresh air and call a physician. In case of eye contact, flush immediately with large amounts of water.

SECTION VI - REACTIVITY DATA

Chemical Stability: Stable Conditions to avoid: None

Incompatibility (Materials to avoid): None

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, phosphene, hydrochloric acid.

Hazardous Polymerization: None

SECTION VII - LEAK AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IF CONTAINERS ARE LEAKING OR LARGE AMOUNTS ARE RELEASED: Remove ignition sources., avoid breathing vapors or skin contact.

Soak up with absorbant material and dispose as gasoline soaked rags.

WASTE DISPOSAL METHOD: Do not puncture or incinerate containers. Give empty, leading or full containers to a disposal service equipped to safely handle and dispose of pressurized containers.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type): NA

VENTILATION	LOCAL EXHAUST (Hoods, Fans, etc.): NA
	MECHANICAL (General Area Ventilation): Should be on if spraying large amounts.

PROTECTIVE GLOVES: NA	EYE PROTECTION: Do not spray toward eyes.
-----------------------	---

OTHER PROTECTIVE EQUIPMENT: None


SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store where temperatures could exceed 54°C (130°F).

OTHER PRECAUTIONS:

SPECIAL PRECAUTIONARY STATEMENTS: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

Date Filled Out: 11-21-85

Prepared or Approved by: 

The accuracy of data and information given on this form is not guaranteed, but it has been filled out to the best of our knowledge and belief. If you find any errors, or have any suggestions to improve the presentation, please contact us at the address given on the first page.

PRODUCT TRADE NAME:

PRODUCT DESCRIPTION: