
U.S. Department of Labor

Occupational Safety and Health Administration



			PREPARED & SIGNED O			
			James R. Bergener			
Section (· · · · · · · · · · · · · · · · · · ·			1		· · · · · · · · · · · · · · · · · · ·
Manufacturer's Name			(312) 352-2565			none Number
Address (Number, Street,	AT PROCESS COMPANY City State and ZIP Code)		(800) 323-3040 TOL: Chemical Name	L FREE OUTSIDE	<u>ILL</u>	INOIS
9600 W. OGDEN A				APPLICABLE		
P. O. BOX 10A			Trade Name and Synonyms GESTETNER	STENCIL CEMENT		
LA GRANGE, \IL	60525		Chemical ALCOHOL PO	LYMER MIXTURE		
Section II - Hazardous I	ngredients					
Paints, Preservatives, en	id Solvents	% TLV (Unit:	t) Alloys and Metallic Coatings			•
Proments		T	Başe Mela)		7	TLV (Units)
					1	
Catalyst 7.			Alloys			
Vehicle			Metallic Coatings			
Solvents			Filler Metal Plus Coating or Core Flux	\times		
Additives		 	Others		-	2.00.000
Others					>	100003
Hazardous Mixtures of C	Other Liquids, Solids or Gases			· .		
	and Educat solids of Classes					TI W (Uman)
C.A.S. # 71-36-	-3 N. BUTYL ALCOHOL			>	T	TLV (Units)
C.A.S. # 64-17-	-5 SDA3A ALCOHOL				<u> </u>	1000 pp
OTHER SUBSTANC	ES DO NOT CONFORM T	O DEPARTMEN	T OF TRANSPORTATION H	AZARD	-	FF
MATERIAL & IS	A NON-REGULATED MAT	ERIAL BY DE	FINITION IN 29CFR1910	.1200.	1	į
lection (II - Physical Dal	ta .					
Soiling Point (*F)	CALCULATED	221°F	Specific Gravity (H ₂ O=1)	0.050		
/apor Pressure (mm Hg.)	0.1110011111111111111111111111111111111	ZZII	CALCULATED Percent Volatile by Volume (%)	@ 25°C	0.8	895
	NOT AVAILABLE		LIQUID		84%	
/apor Density (AIR≠1)	CALCULATED	2.1	Evaporation Rate	OT AVAILABLE		-
olubility in Water INSOLUBLE					<u> </u>	
Appearance and Odor DARK BROWN LIQU	ID - ALCOHOL ODOR			<u> </u>		
ection IV - Fire and Exp	losion Hazard Data				<u> </u>	
esh Point (Method Used)	T.C.C. APPROX. 68	°F - 78°F	Flammable Limits	Lei 1.4	Uei	19
xtinguishing Media VATER SPRAY, DR	Y CHEMICAL, ALCOHOL	FOAM. CARI	SON DIOXIDE	 	<u>. </u>	
pecial Fire Fighting Proced	D TO KEEP FROM SPRE			F-CONTAINED BR	EATE	ITNG
APPARATUS.			The state of the s	- VVIIIIIII DI		. 2413
nusual Fire and Explosion		URCES. Her	E ADEQUATE VENTILATION			
		-2000, 001	. WORKOWIE ABUITEWITON	•		

étlen V . Heeft	Material Date			THE THE AND INCREDIENT OF	
reshold Limit Va	lu#		# 17 TATO	DENCE THAT ANY INGREDIENT OF	
EE SECTION	ON II		THIS PRODUCT CAUSES AN INC	CREASED CANCER RISK IN HUMANS. VSINESS,& THROAT IRRITATION. SKIN: LEBELTATION INCESTION: DEPRESSION	
cts of Overext	xosure INHAL	ATI	OF SKIN. EYES: TEMPORARY	IRRITATION. INGESTION: DEPRESSION	
RRITATIO	N, DEFAILI	CVC	TEM, VOMITING.		
				TO THE PARTY OF THE CTOPPEN	
ergency First	Nd Procedures]	NHA	LATION: REMOVE TO AIR FREE	OF VAPORS; IF BREATHING HAS STOPPED,	
DMINISTE	R ARTIFICE	ΑL	RESPIRATION CALL A PHYSICIA	AN. SKIN: KEMOVE CONTAINED FOR 15 MINU	
HOES; WA	SH AFFECTI	ID A	REAS WITH SOAP & WATER. EN	YES: FLUSH WITH COOL WATER FOR 15 MINUTION: IF VICTIM IS CONSCIOUS & ABLE TO OF PHYSICIAN OF POISON CONTROL CENTER	
F TRKITA	TION PERS	3 W/	TER TO DILUTE. ON ADVICE	OF PHYSICIAN or POISON CONTROL CENTER	
MALLON, NI.Y IND	UCE VOMIT	LNG			
ction YI - Rec	ctivity Data			and the second of the second o	
outy	Unstable		Conditions to Avoid		
	Stable	Х			
compatability ()	Materials to Avoid	1)			
Tarrente Decor	noosition Produc	ts	TWO COMPLICATION		
ARBON DI		FOR	MED DURING COMBUSTION.		
szardous plymerization	May Occur		Conditions to Avoid		
	Will Not Occur	X	NOT AVAILABLE		
	<u> </u>				
aste Disposal	Method	ን ለ ጥ ገ	ON OR SANITARY LANDFILL DI	SPOSAL IN ACCORDANCE WITH LOCAL, STATE	
	L REGULAT:				
	Ipecial Protection				
	lection (Specify I ANTITIES:	iypel Δ`	PPROVED NIOSH/MESA RESPIRAT	OR	
LARGE QU	Local Exhaus			Special	
			N LEVELS BELOW 1000 ppm	NONE	
Mechanical (General)			(al)	Other	
		МО	NE LE	NONE	
Protective Glov	SE QUANTIT	IES	1 7 7	FOR LARGE QUANTITIES	
			-SAFETY SHOWERS & EYE WASH	STATIONS ARE RECOMMENDED.	
FOR LARC	GE QUANTITI	TES	-OMFELL BHOWERD & ELE WAOII		
N	Se Taken in Hai	adlino	and Storing		
KEEP AWA	AY FROM HE	AT,	OPEN FLAMES & SMOKING MATE	ZRIALS.	
Other Precaut	ions			CONTAINERS	
AVOID P	ROLONGED I	3RE/	ATHING OF VAPORS. AVOID PRO	OLONGED SKIN CONTACT. KEEP CONTAINERS	
TN COOT	, VENTILA	תקיו	AREAS.		
TW COOP	, , ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			Form	