MSDS: **B5703**

ITEM: 4LRF8 - Penetrating Solvent HD Size 11 Oz LP NUMBER: U848669474 ORDER: 0103775691

MATERIAL SAFETY DATA SHEET (MSDS)

Associated Grainger Items 4LRF8, 4LRG2

"BLASTER (R*) "

MSDS

MATERIAL SAFETY DATA SHEET

THE BLASTER CORPORATION

PB PENETRATING CATALYST

MSDS NUMBER: PB - AEROSOL

REVISION DATE: 10/16/07

1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PB PENETRATING CATALYST

REVISION DATE: 10/16/07

MSDS NUMBER: PB - AEROSOL

COMMON NAME: PB BLASTER

PRODUCT CODE: 16-PB, 8-PB, 8-PBS, PBTS, 20-PB, 26-PB

THE BLASTER CHEMICAL COMPANIES, INC. 8500 SWEET VALLEY DRIVE VALLEY VIEW, OHIO 44125

(216) 901-5800

(216) 901-5801 FAX

WWW.BLASTERPRODUCTS.COM

24 HOUR EMERGENCY CONTACT: CHEMITREC: (800) 424-9300

- 2 COMPOSITION/INFORMATION ON INCREDIENTS

HAZARDOUS INGREDIENTS

CAS #

PERCENT

EXPOSURE LIMITS

ALKYLOXYPOLYETHYLENEOXYETHANOL

0 - 3%

OSHA (TWA): N/E ACGIH (TLV): N/E

SOLVENT NAPHTHA, HEAVY AROMATIC**

64742-94-5 40 - 50%

OSHA (TWA): N/E ACGIH (TWA): N/E

HEAVY PETROLEUM DISTILLATE

64742-65-0 20 - 30% OSHA (TWA): N/E ACGIH (TLV): N/E

LIGHT DISTILLATE

64742-47-8 30 - 40%

OSHA (TWA): N/E ACGIH (PEL): 500 PPM

*DENOTES CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE 1986 SUPERFUND AMENIMENTS AND REAUTHORIZATION ACT (SARA) AND 40 CFR PART 372.

**ARCMATIC NAPHTHA CONTAINS 1-7 % NAPHTHALENE (91-20-3) AND 0-1% PSEUDOCUMENE (95-63-6)

- 3 HAZARDS IDENTIFICATION

ROUTE OF ENTRY: EYES, SKIN, INHALATION, INGESTION

TARGET ORGANS:

INHALATION: INHALATION OF SPRAY MIST MAY CAUSE IRRITATION TO THE RESPIRATORY TRACT.

SKIN CONTACT:
REPEATED OR PROLONGED CONTACT WITH SKIN MAY CAUSE MILD IRRITATION AND
POSSIBLY DERMATITIS.

EYE CONTACT:
LIKELY TO CAUSE IMMEDIATE OR DELAYED IRRITATION, IRRITATION WILL SHOW AS REDNESS AND/OR SWELLING OF THE EYES.

INGESTION: INGESTION MAY CAUSE IRRITATION TO THE MOUTH, ESOPHAGUS AND STOMACH. MAY AGGRAVATE PRE-EXISTING SKIN AND RESPIRATORY DISORDERS.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED COCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE, INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR

- 4 FIRST AID MEASURES -

INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

CONTINUE TO MONITOR. GET MEDICAL ATTENTION.

SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING IMMEDIATELY!

MIE CONTACT: FLUSH SYE(S) WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. IF EYE IRRITATION PERSISTS, OBTAIN MEDICAL TREATMENT.

DO NOT INDUCE VOMITING!
GET MEDICAL ATTENTION IMMEDIATELY!

- 5 FIRE FIGHTING MEASURES

FLASH POINT: 155 DEG. F ASTM D-56 (TCC)

EXTINGUISHING MEDIA:
DRY CHEMICAL, CARBON DIOXIDE OR FOAM IS RECOMMENDED. WATER MAY BE
INEFFECTIVE FOR EXTINGUISHMENT, BUT CAN BE USEFUL IN MINIMIZING OR
DISPERSING VAPORS, PROTECTING PERSONNEL AND COOLING CONTAINERS. IF
CONTAINERS ARE NOT PROPERLY COOLED THEY CAN RUPTURE IN THE HEAT OF A FIRE.
AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

UNUSUAL FIRE & EXPLOSION HAZARDS:

LEVEL 3 AEROSOLS - CONTENTS UNDER PRESSURE!

— 6 ACCIDENTAL RELEASE MEASURES -

LEAKING AEROSOL CANS SHOULD BE PUT INTO SUITABLE CONTAINER UNTIL THE INTERNAL PRESSURE HAS DISSIPATED. USE SUITABLE ABSORBENTS TO COLLECT LIQUID PRODUCT. CONSULT REGULATIONS FOR THE DISPOSAL OF THE CONTAINER, LIQUID AND

— 7 HANDLING AND STORAGE -

HANDLING PRECAUTIONS:
USE IN ACCORDANCE WITH GOOD INDUSTRIAL WORKPLACE PRACTICES. AVOID UNNECESSARY CONTACT.

WASH THOROUGHLY AFTER HANDLING, USE WITH GOOD VENTILATION.

STORE IN A DRY PLACE AWAY FROM EXCESSIVE HEAT. STORE CONTAINERS WITH LIDS ON AND PROPERLY LABELED.

DO NOT STORE AT TEMPERATURES ABOVE 120 DEGREES F.

— 8 EXPOSURE CONTROLS/PERSONAL PROTECTION -

ENGINEERING CONTROLS:
EYE WASH STATIONS AND EMERGENCY SHOWERS SHOULD BE IMMEDIATELY AVAILABLE.

PROTECTIVE EQUIPMENT:

EYES AND FACE: STANDARD SAFETY GLASSES WITH SPLASH SHIELDS TYPICALLY OFFER ADEQUATE PROJECTION. WHERE EXCESSIVE SPLASHING OR SPRAYING IS POSSIBLE, A FACE SHIELD SHOULD BE USED.

SKIN AND CLOTHING: EXCESSIVE CONTACT SHOULD BE AVOIDED. NEOPRENE GLOVES, BOOTS AND APRONS WILL PROVIDE ADEQUATE PROTECTION WHEN CONTACT CANNOT BE AVOIDED. REMOVE AND WASH ANY CONTAMINATED CLOTHING IMMEDIATELY. WASH THOROUGHLY AFTER HANDLING.

RESPIRATORY:
GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT TO CONTROL AIRBORNE LEVELS.

MAINTAIN ATREORNE CONCENTRATIONS BELOW OSHA ESTABLISHED EXPOSURE LIMITS OF INGREDIENTS IN SECTION 2.

EXPOSURE GUIDELINES/OTHER

EXPOSORS GUIDBLINES/OTHER:
THE BLASTER CHEMICAL COMPANIES TAKES NO RESPONSIBILITY FOR DETERMINING WHAT
MEASURES ARE REQUIRED FOR PERSONAL PROTECTION IN ANY SPECIFIC APPLICATION,
THIS INFORMATION SHOULD BE USED WITH DISCRETION.

9 PHYSICAL AND CHEMICAL PROPERTIES -

APPEARANCE: ORANGE VISCOUS OILY

PHYSICAL STATE: LIQUID

ODOR: HEAVY AROMATIC

OH: NOT DETERMINED

VAPOR PRESSURE: NOT DETERMINED

VAPOR DENSITY: >1 (AIR = 1)

BOILING POINT: 352 F

FREEZING/MELTING PT.: NOT DETERMINED

SPEC GRAV./DENSITY: 0.87 (WATER = 1)

HEAT VALUE: NOT DETERMINED

VOC: NOT DETERMINED

EVAP. RATE: <1 (NBA=1)

BULK DENSITY: NOT DETERMINED

OCTANOL: NOT APPLICABLE

MOLECULAR WEIGHT: NOT DETERMINED PARTICLE SIZE: NOT APPLICABLE SOFTENING POINT: NOT APPLICABLE VISCOSITY: NOT DETERMINED PERCENT VOLATILE: NOT DETERMINED SAT. VAP. CONCENTRAT.: NOT DETERMINED MOLECULAR FORMULA: NOT DETERMINED - 10 STABILITY AND REACTIVITY -STABILITY: THIS PRODUCT IS STABLE. CONDITIONS TO AVOID: VOID EXCESSIVE HEAT, SOURCES OF IGNITION AND EXCESSIVE WATER. MATERIALS TO AVOID (INCOMPATIBILITY):
VOID CONTACT WITH STRONG OXIDIZING AGENTS AND STRONG REDUCING AGENTS (STRONG ACIDS OR BASES.) AVOID MIXTURE WITH WATER. HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, AND VARIOUS HYDROCARBONS. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR. - 11 TOXICOLOGICAL INFORMATION TOXICOLOGICAL INFORMATION ON THIS PRODUCT AS A MIXTURE HAS NOT BEEN DETERMINED. SEE SECTION 15 FOR REPORTABLE INGREDIENTS. - 12 ECOLOGICAL INFORMATION -ECOLOGICAL INFORMATION ON THIS PRODUCT AS A MIXTURE HAS NOT BEEN DETERMINED. - 13 DISPOSAL CONSIDERATIONS -USED OR UNUSED PRODUCT SHOULD BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. SOME SPECIAL REGULATIONS MAY EXISTS FOR THE DISPOSAL OF EMPTY AEROSOL CONTAINERS. EMPTY CONTAINERS MAY CONTAIN RESIDUAL PRESSURE AND CONTENTS. THEY SHOULD BE HANDLED WITH THE SAME PRECAUTIONS AS THE PRODUCT. - 14 TRANSPORT INFORMATION -DEPT. OF TRANSPORTATION (DOT):
THIS PRODUCT, AS IT LEAVES BLASTER'S FACILITIES, MEETS THE DEFINITIONS SET
FORTH IN CER 49 PART 173.150C AS A "CONSUMER COMMODITY." ALLOWING FOR
CERTAIN EXCEPTIONS (173.156) FOR DOMESTIC SURFACE (GROUND) SHIPMENTS. PROPER SHIPPING NAME: CONSUMER COMMODITY HAZARD CLASS: ORM-D INTERNATIONAL (IMDT-IATA): PROPER SHIPPING NAME: AEROSOLS, LIMITED QUANTITIES HAZARD CLASS: 2 FLAMMABLE COMPRESSED GAS UN NUMBER: 1950 — 15 RECULATORY INFORMATION -COMPONENT / (CAS/PERC) / CODES: *DISTILLATES, PETROLEUM, SOLVENT-DEWAXED HEAVY PARAFFINIC (64742650 40-60%) *CARBON DIOXIDE (PROPELLANT) (124389 0-3%) MASS, OSHAWAC, PA, TXAIR REGULATORY KEY DESCRIPTIONS: MASS: MA MASSACHUSETTS HAZARDOUS SUBSTANCES LIST OSHAWAC: OSHA WORKPLACE AIR CONTAMINANTS PA: PA RIGHT-TO-KNOW LIST OF HAZARDOUS SUBSTANCES TXAIR: TX AIR CONTAMINANTS WITH HEALTH EFFECTS SCREENING LEVEL — 16 OTHER INFORMATION — MANUFACTURER'S DISCLAIMER:
TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE.
HOWEVER, NEITHER THE BLASTER CHEMICAL COMPANIES MOR ANY OF ITS SUBSIDIARIES
ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE
INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY
MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT
UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. ALIHOUGH CERTAIN HAZARDS
ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARD HEALTH FIRE

WHICH EXISTS. HMIS RATINGS:

REACTIVITY 0 NFPA RATINGS: HEALTH 2 FIRE REACTIVITY 0