

### Material Safety Data Sheet Van Son Blanket Fix

MSDS Sheet # 3-3 Date: 9-29-1995

	14	M	ı	5	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	2 1 0

Material Safety and Data Sheet prepared by G. Lindquist, Consultant

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### MANUFACTURER:

Van Son Holland Ink Corporation of America 92 Union Street, Mineola, NY 11501

Emergency Telephone:516-294-8811 Product Class: Blanket Repair Material Trade Name: Van Son Blanket Fix

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer's Code ID:VS2004

# 2. INGREDIENT COMPOSITION INFORMATION

Ingredient		CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	<del>-</del>
Continue					1100(120)	- Caranoge
Cyclic Amine	· ·	872-50-4	95	N/A	N/A	No
Hydroxy Propyl Cellulose		9004-64-2	2-5	N/A	N/A	No
					<del> </del>	<del></del>
				<u> </u>		
			· · · · · · · · · · · · · · · · · · ·	<del></del>		
				·		
				<del>                                     </del>	<del>                                     </del>	<del>                                     </del>
		·		<del> </del>		<del> </del>

# 3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200 ......None

#### 4. FIRST AID MEASURES

#### **EFFECTS OF OVEREXPOSURE**

Skin Contact ......Prolonged contact or repeated exposure may cause blistering.

nasal and respiratory passages.

Ingestion ........May cause gastrointestinal irritation and diarrhea.

Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.

Target Organs: ......Skin, eyes, lungs, liver and kidneys.

Primary Routes of entry ......Eyes, inhalation, dermal.

### **EMERGENCY FIRST AID PROCEDURES**

If irritation persists, contact a physician.

Wash affected skin areas with soap and water.

Seek medical attention if irritation persists.

• Inhalation .......Remove individual to fresh air.

## 5. FIRE FIGHTING MEASURES

Flash Point TCC ......Above 195° F. Method used: Closed cup.

Explosion Limits.....LEL: 1.3 / UEL: 9.5

Extinguishing Media ......Foam, carbon dioxide, dry chemical fire apparatus.

Water spray may be applied to cool exposed closed containers.

Unusual Fire and Explosion Hazards......Dense smoke may be generated when burning.

Thermal decomposition causes toxic fumes.

Special Fire Fighting Procedures......Self-contained breathing apparatus recommended.

## 6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers. Vapors may ignite. Material partly water soluble. May float and spread.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

### 7. HANDLING AND STORAGE

Handling:

Avoid storage above 90°F.

Keep containers closed when not in use to prevent degradation by moisture.

Other Precautions: Do not breathe vapors. Do not get in eyes.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:

Use sufficient ventilation.

Protective Gloves:

Impermeable gloves recommended to prevent skin irritation and absorption.

**Respiratory Protection:** 

NIOSH Respirator during prolonged use.

**Eye Protection:** 

Safety glasses are recommended.

Other Protection:

Apron, if splashing is possible.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs)	1.68 lbs./gallon	200 Grams/liter Method 24
Boiling Range °F:> 396	, 3	Freezing Point °F: N/A
Vapor Density vs. Air: Heavier		Vapor Pressure: 0.29mm Hg
Density: 8.60 lbs./ gallon ASTM D1475		•
Specific Gravity: 1.03	·	
Type of Odor: Amine Like	· <u>, , </u>	Odor Threshold: High
Appearance: Gel		<b>pH:</b> 10-11
Evaporation Rate vs. Butyl Acetate: Slower		•
Coefficient of Water/oil Distribution: N/A		1
Percentage Volatile By Weight: 95% ASTM D2	2369	

### 10. STABILITY AND REACTIVITY

**Product Stability:** 

Stable

**Conditions to Avoid:** 

Strong oxidizing agents, acids and bases. Avoid storage above 90°F.

Keep containers closed when not in use.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and smoke.

Hazardous Polymerization: Will not occur.

#### MSDS#3-3: Van Son Blanket Fix

# 11. TOXICOLOGICAL INFORMATION

# 12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

## 13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

# 14. TRANSPORT INFORMATION

DOT (HM 181): Combustible Liquid N.O.S. NA1993 (NMP) Packaging Group III

Shipping Labels: Combustible Liquid N.O.S.

# 15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)

All ingredients listed in TSCA Inventory

CERCLA Superfund 40CFR 117.302

Contains no reportable materials

SARA Title III

None

FDA

This product is not a food additive and would not have approval for direct or indirect contact with food.

EINECS (European Economic Community)

All ingredients listed.

California Proposition 65

None

CONEG Legislation

Meets all current State Heavy Metal limitations.

Canadian WHMIS

Non controlled product

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.