

# MATERIAL SAFETY DATA SHEET

## FOR PRINTING INK AND RELATED MATERIALS

INFORMATION ON THIS FORM IS PROPRIETARY INFORMATION AND FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS

DATE OF PREP Aug 1 1987 PREPARED BY J. Haafkens

### HAZARD RATINGS

Minimal..... 0  
Slight..... 1  
Moderate..... 2  
Serious..... 3  
Severe..... 4

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

### Section I

MANUFACTURERS NAME: Van Son Royal Dutch Printing Ink Factories Distributor: Van Son Corp of America  
STREET ADDRESS: 97 Union Street CITY, STATE AND ZIP CODE: Mineola, NY 11501  
EMERGENCY TELEPHONE NUMBER: 516-294-8811  
PRODUCT CLASS: II B. Offset Ink Non Oxidizing Black 10923  
TRADE NAME: Rubberbase Plus Offset Ink MANUFACTURER'S CODE IDENTIFICATION: Black 12630 VS310  
Black 10850

### Section II - HAZARDOUS INGREDIENTS

Ingredient:	Hazard Data:
Carbon Black Petroleum Hydrocarbon	CAS 1333-86-4 CAS 64742-46-7  These ingredients are listed on some state Right to Know lists. They are not on the Federal list  OSHA PEL for oil mist 5mg. per cubic meter ACGIH TLV not established

### Section III - PHYSICAL DATA

BOILING RANGE F 500 <sup>o</sup> F - 600 <sup>o</sup> F	VAPOR DENSITY: HEAVIER X vs. air LIGHTER I	LIQUID DENSITY: HEAVIER X vs. water LIGHTER I	TYPE OF ODOR oily odor
APPEARANCE Black Paste	EVAPORATION RATE FASTER I vs. Butyl Acetate SLOWER X	PERCENT VOLATILE WT. @ 72 F. NIL	

### Section IV - FIRE & EXPLOSION DATA

FLAMMABILITY CLASSIFICATION	OSHA III B DOT N. Regl.	FLASH POINT <u>11 F. th. 200<sup>o</sup>F</u> (Method Used) Open Cup	LEL N.A
-----------------------------	----------------------------	---	------------

#### EXTINGUISHING MEDIA

OAM       ALCOHOL FOAM       CO2       DRY CHEMICAL       WATER FOG       OTHER

#### UNUSUAL FIRE AND EXPLOSION HAZARDS

None

#### SPECIAL FIREFIGHTING PROCEDURES

None

